

Blaze Warrior 10/10

Ultra-Lightweight High-Performance Portable Fire Pump

Godiva — IDEX Fire & Safety

Technical Specification Sheet

Performance & Technical Specifications

Rated Flow	1,000 L/min (264 USGPM)
Rated Pressure	10 bar (145 PSI)
Max Flow (3 bar)	Over 1,400 L/min
Suction Lift	3 metres (standard)
Engine	Vanguard 40 HP 4-stroke V-twin EFI/ETC
Engine Cooling	High-efficiency air/oil system
Weight (dry)	125 kg
Volume	0.24 m ³
Fuel Tank	15.4 L integral moulded tank with fuel gauge
Starting System	Electric start with recoil backup
Priming System	Dry piston primer
Battery	Lithium-ion battery
Discharge	Standard 2× 75 mm BS connections
Suction	Standard 110 mm BS connection
Operating Temp	-20°C to +50°C
Standards	EN 1028 / PFPN10-1000

Key Features

- Fully compliant with EN 1028 / PFPN10-1000 — certified for civil defence and fire service use
- Advanced high-efficiency cooling system for continuous uninterrupted operation
- Optimised ergonomics with DIN tray mounting lugs for rapid vehicle loading
- Extendable LED light mast for night operations
- Engine hours meter and Malfunction Indicator Light (MIL) LED
- Significantly lighter and more compact than comparable EN 1028 certified pumps
- Electric fuel injection (EFI) for reliable cold-start performance

Certifications: EN 1028, PFPN10-1000

For full performance curves and latest specifications, visit www.godiva.co.uk

Authorised Distributor — Fire & Rescue Tech | inquiry@fireandrescuetech.com | www.portablefirefightingpumps.com

Specifications subject to change without notice. Contact distributor for latest data. Images for illustration purposes.