

PowerFlow HPX300-B18

High-Flow Engine-Driven Fire Pump

Hale Products / Godiva
— IDEX Corporation
Technical Specification Sheet

Performance & Technical Specifications

Flow at 50 PSI	400 GPM (1,514 L/min)
Flow at 75 PSI	300 GPM (1,136 L/min)
Flow at 100 PSI	190 GPM (719 L/min)
Max Flow	400+ GPM
Engine	Briggs & Stratton 18HP 4-cycle V-Twin
Engine Type	Gasoline, 4-stroke
Pump Body	Hard-anodized aluminum
Impeller	Bronze with renewable wear rings
Starting System	Electric + recoil backup
Priming System	Exhaust gas venturi
Mechanical Seal	Self-adjusting
Standards	NFPA 1906, CE

Key Features

- High-flow design suited for low-pressure water supply and water transfer operations
- Large capacity 400 GPM at 50 PSI — ideal for wildland tanker support and relay pumping
- Same compact, portable form factor as HPX200 series
- Hard-anodized aluminum body for maximum durability and corrosion resistance
- Electric start standard with recoil backup for field reliability

Certifications: NFPA 1906, CE

Also available with Kubota KBD24 diesel engine (HPX300-KBD24)

Authorised Distributor — Fire & Rescue Tech | inquiry@fireandrescuetechnology.com | www.portablefirefightingpumps.com
Specifications subject to change without notice. Contact distributor for latest data. Images for illustration purposes.